

UltraSafe Series UltraSafe-260 - 2 mil clear



Image is only representative

Product Description

UltraSafe 2 Mil is a premium grade safety and security polyester film with a scratch resistant coating and pressure sensitive adhesive.

Specifications

Specifications	
Product Code	UltraSafe-260
Product Family	UltraBlock
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Width(s)	60"
Length	100 linear feet (30.5m)
Thickness	2 mil
SOLAR PROPERTIES:	
Reflectance	10%
Visible Light Transmission	83%
UV Rejection	99%
Total Solar Reflectance	8%
Total Solar Absorbance	15%
PHYSICAL PROPERTIES	
Tensile Strength psi	32,500
Yield Strength psi	12,000
Break Strength Ibs/inch TD/MD	182/217
Longitude Elongation at Break	>100%
Peel Strength g/inch	2750
Puncture Resistant Load Ibs	9320

Product Construction

Face Film Adhesive Release Liner 2 mil polyester Clear, Pressure-sensitive Silicone

Product Details

UltraSafe-260 - Our 2Mil safety film is an optically clear polyester film with an aggressive adhesive that molecularly bonds the film with the glass. Included in the construction is an interior layer of ultra violet screening that allows for 99% rejection of damaging ultra violet rays and on the outer surface is one of the strongest scratch resistant coatings in our industry.

Installation and Warranty

Installation

Installation should be in accordance with manufacturer's installation instructions.

Warranty

This **UltraSafe**® product will be free from defects in material and manufacture for a period of ten (10) years from the date of installation. See warranty information for specific details

Flammability Rating for **UltraSafe**® Polyester films with adhesive: When applied to surfaces- glass or plastic sheet: Horizontal Burn (Flame Spread) ASTM D-635 inch < 1.0 UL 94 Rating UL 94 UL Classification V-O Class A 0 -25 Flame Spread Index 0 -450 Smoke Developed Index

Product Distribution and Contact Information

UltraSafe® Decorative Films are available through qualified Installing Dealers, Distributors or from Decorative Films, LLC. Samples submitted upon request.

Contact Information

Decorative Films, LLC 1-888-657-5224 www.decorativefilm.com